



C248 POWERTRAIN CONTROL MODULE (PCM)

PIN	CIRCUIT	CIRCUIT FUNCTION	PIN	CIRCUIT	CIRCUIT FUNCTION
1A	84 (BL/R)	Keep Alive Power	1L	715 (R/W)	Data Link Connector (DLC)
1B	702 (R/BK)	PCM Power	1M	369 (GN/R)	Vehicle Speed Sensor Input (+)
1C	712 (W/R)	Data Link Connector (DLC)	1N	718 (BR/Y)	Power Steering Pressure Input
1D	12 (BK/R)	Manual Lever Position Switch Input ("P" and "N" Ranges)	1O	663 (P)	Rear Window Defrost On Input
1E	746 (BL)	Malfunction Indicator Lamp Output	1P	196 (O/BK)	Blower Motor On Input
1F	321 (W/GN)	Brake Input	1Q	824 (PK/GN)	Overdrive Off indicator Output
1G	711 (LG/R)	Data Link Connector (DLC)	1R	185 (PK/BK)	A/C On/Off and Low Pressure Input
1H	823 (BR/BK)	Overdrive Off Switch Input	1S	187 (GN/BK)	A/C Relay Output
1I	750 (BL/O)	Distributor Igniter Output	1T	814 (BR)	Idle Switch Input
1J	261 (W)	Headlamps On Input	1U	702 (R/BK)	PCM Power
1K	272 (GN)	DRL Module Input	1V	18 (GN)	Start Signal Input